



REQUEST FOR QUOTATION

The Civil Aviation Authority of the Philippines (CAAP-Main Office), through its Canvass and Contract Committee (CCC), will undertake a **Small Value Procurement** for the “Supply and delivery of RG-11 F-Connectors for Airports/Remote Sites with VSAT Installations” in accordance with Section 53.9 of the Implementing Rules and Regulations of Republic Act No. 9184.

RFQ No. : C23-026-05
Name of Project : Supply and delivery of RG-11 F-Connectors for Airports/Remote Sites with VSAT Installations

Approved Budget for
for Contract : P388,080.00
Terms : See the attached Annex “A” for Terms of Reference and
corresponding Specifications

Location : Procurement Division, CAAP, MIA Road, Pasay City
Delivery Term : Fourteen to Sixteen (14-16) weeks from the receipt of Notice for
Compliance : Partial delivery is not allowed
Delivery Location : CAAP Head Office Warehouse (Supply Division)
Delivery Time : 8:00 AM – 4:00 PM (working days)

Interested suppliers are required to submit their valid and current documents which must be properly fastened and sealed in an envelope:

1. Mayor’s or Business Permit issued by the city or municipality where the principal place of business of the prospective bidder is located, or the equivalent document for Exclusive Economic Zones or Areas;
2. Income Business Tax Return for ABC’s above P500,000.00;
3. PHILGEPS Certificate of Registration;
4. Tax Clearance;
5. Notarize Omnibus Sworn Statement (GPPB prescribed Form) for ABC’s above P50,000.00; (Authorized representative must attach Special Power of Attorney (SPA) for Sole Proprietorship Certificate for Corporation)
6. Price quotation from (Annex “A”) during submission of offer/Quotation and,
7. Brochure if applicable

The winning supplier shall – upon claiming of the Contract – present the original copy of the documents listed above for comparison, or submit a **Certified True Copy** of the original document which must be certified by the issuing government agency. However, the **original copy** of the Omnibus Sworn Statement, Price Quotation Form, and Brochure **must be included in the sealed bid**.

Price quotation/s must be valid for a period of one hundred twenty (120) calendar days from the date of submission.

Quotations exceeding the Approved Budget for the Contract shall be rejected.

Award of contract shall be made to the lowest quotation, which complies with the minimum description as stated above and other terms and conditions stated in the price quotation form. In case two or more bidders are determined to have submitted the Lowest Calculated/Lowest Calculated and Responsive Quotation, CAAP-CCC shall adopt and employ “draw lots” as the tie breaking method to finally determine the single winning provider in accordance with GPPB Circular 06-2005.

The CAAP-TIAC shall have the right to inspect and/or test the goods to confirm their conformity to the technical specifications.

Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by the bidder or his/her duly authorized representative/s.

Liquidated damages equivalent to one tenth of one percent (0.1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. CAAP shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.


ATTY. JOHN BEAU B. MASIGLAT
CCC-Chairperson



PRICE QUOTATION FORM

Date: _____

The Chairperson
 Canvass and Contract Committee
 Procurement Division, CAAP,
 MIA Road, Pasay City

Sir:

After having carefully read and accepted the terms and conditions in the Request for Quotation, hereunder is our quotation/s for the item/s as follows:

Technical Specification	QTY	Unit	Unit Price	Total Price
Supply and delivery of RG-11 F-Connectors for Airports/Remote Sites with VSAT Installations SNS/716SNS1P11H Univ. RG11 F-Connector Standard or Quad-Shield Pro SNS RG 11 Universal "F" Coaxial Compression Connector 7/16" Hex Head, Polymer Compression Sleeve for easy insertion & lowest possible tool compression Specification: Cable: RG-11/U Conductor Size: 14 AWG Color Band: Black Type: 75 Ohm Environmental Space: Indoor/Outdoor Temperature Range: -40°F (-40°C) to 140°F (-40°C) Mechanical Characteristics: Termination Type: Compression Cable Center Conductor Diameter Limits: 0.0634 – 0.0647 inch Cable Dielectric Diameter Limits: 0.280 0.294 inch Cable Insertion Force: 20lbf	600	pcs		
Total (Inclusive of VAT)				

(Amount in Words) _____

The above-quoted prices are inclusive of all costs and applicable taxes.

Very truly yours,

 Name/Signature of Representative

 Position

 Name of Company

 Contact No.

 Email Address



TERMS OF REFERENCE

Name of Project	: Supply and Delivery of RG-11 F-Connectors for Airports/Remote Sites with VSAT Installations
Approved Budget	: PhP 388,080.00
Delivery Period	: 14 – 16 weeks from the receipt of Notice for Compliance <i>Note: Partial delivery is not allowed.</i>
Delivery Location	: CAAP Head Office Warehouse <i>Note: Delivery must be made only from 8:00AM-4:00PM during regular work days.</i> <i>A Written Notice must be sent to the official email address of the Procurement Division, and Supply Division at least seven (7) calendar days prior to the intended date of delivery.</i> <i>A confirmation of availability of concerned office must be received by the supplier before proceeding with the delivery. None compliance may be a ground for refusal of entry to the premises and receipt of delivery with no fault on the part of the Civil Aviation Authority of the Philippines.</i>
Terms of Payment	: Payment upon full delivery and subject to usual government accounting rules and regulations.

Technical Specifications:

SNS/716SNS1P11H

Univ. RG11 F-Connector

Standard or Quad-Shield

ProSNS RG 11 Universal “F” Coaxial Compression Connector

7/16” Hex Head, Polymer Compression Sleeve for easy insertion & lowest possible tool compression



Specifications:

Cable: RG-11/U
Conductor Size: 14 AWG
Color Band: Black
Type: 75 Ohm
Environmental Space: Indoor/Outdoor


Temperature Range:

-40°F (-40°C) to 140°F (-40°C)

Mechanical Characteristics:

Termination Type: Compression
Cable Center Conductor Diameter Limits: 0.0634 – 0.0647 inch
Cable Dielectric Diameter Limits: 0.280 – 0.294 inch
Cable Insertion Force: 20lbf

Prepared by:


MIRAFIOR V. ANDAYA
CNSS Officer IV
CMMID-ANOD

Approved by:


FLORIAN S. ATIENZA
Div. Chief III
ANOD