



#### REQUEST FOR QUOTATION NO.: RFQ-2024-025

| Date: | July | 1, | 2024 |
|-------|------|----|------|
|       |      |    |      |

| Name of the Company       |   | MILL THATE         |
|---------------------------|---|--------------------|
| Address                   | : |                    |
| Contact No.               | : |                    |
| PhilGEPS Registration No. | : | celi di must sulci |

#### Sir/Madam:

Please quote your best offer (lowest net, price, taxes, and government discount terms included) and submit your Quotation duly signed by you or your duly authorized representative not later than July 5, 2024 @ 3:00 PM for:

CONSOLIDATED TOOLS AND EQUIPMENT FOR AREA CENTER the : Name

Project

Location

LAOAG INTERNATIONAL AIRPORT

Terms

of :

Reference

Sealed quotations must be submitted either personally to Ms. Hazelle May C. Andres, Head, Secretariat of the Bids and Awards Committee of Laoag International Airport (BAC-LIA) or e-mail at bac\_area1@caap.gov.ph. For any clarification, do not hesitate to contact us through the contact information seen below.

Aside from the Terms and Conditions provided at the back portion of this RFQ, please observed the following general conditions:

- The following documents must be attached upon submission of the Quotation:
  - a) Mayor's Permit
  - b) PhilGEPS Certificate of Registration
- 2. All quotations shall be considered as fixed price and not subject to price escalation during the contract implementation.
- 3. Payment shall be made through check.

ATTY, RIZZA JON Chairperson, Bids and Awards Committee

After having carefully read and accepted the Terms and Conditions, I/We submit our quotations for the following item/s:

| ITEM DESCRIPTION  | APPROVED                     | PROVED OFFER* |      |               |                   |     |                                |         |  |  |
|---|------------------------------|---------------|------|---------------|-------------------|-----|--------------------------------|---------|--|--|
| (SPECIFY THE BRAND AND MODEL OF YOUR  | BUDGET OF<br>THE<br>CONTRACT | PRICE         |      |               |                   |     | iance w/<br>nnical<br>ications | REMARKS |  |  |
| OFFER/PROPOSAL, IF<br>APPLICABLE)   | (ABC)                        | QTY           | UNIT | Unit<br>Price | Total Price       | Yes | No                             |         |  |  |
| 1. Pressure Washer  > Power: 1,700 W  > Max Pressure: 130 bar  > Max Flow Rate: 420 | ₱11,700.00                   | 1             | Unit | 60.1          | 00,077<br>100,007 |     | Mag and                        |         |  |  |





|         | L/h   | 176                                       | TOTAL .            | DENDAT      | 51753        |              |       |          |                     |
|---------|---|---|--------------------|-------------|--------------|--------------|-------|----------|---------------------|
| A       | Inlet Water   |   |                    | Sal Printed |              |              |       |          |                     |
| >       |   |   | -                  | 100         |              |              |       |          |                     |
|         | Temperature: 40°C   |   |                    |             |              |              |       |          |                     |
| >       | Self Priming  |   |                    |             |              |              |       |          |                     |
|         | Capability: 0.5 m   |   |                    |             |              |              |       | 115.00   |                     |
| >       | Detergent System:   |   |                    |             | Į.           |              |       |          |                     |
|         | High Pressure   |   |                    |             |              |              |       |          |                     |
|         |   |   |                    |             | 1            |              |       | 15M Y    | TERMS .             |
|         | Foam  |   |                    |             |              |              |       |          | THE PERSON NAMED IN |
| >       | Motor Type: Series  |   |                    |             |              |              |       |          |                     |
| >       | Pump Type: 3  |   |                    |             |              |              |       |          |                     |
|         | Cylinder  |   |                    |             |              |              |       | UT L     |                     |
| >       | · · · · · · · · · · · · · · · · · · ·   |   |                    |             |              |              |       |          |                     |
|         | Metal   | Internation                               | 5 10 3             | n 35-16-1   | I the I      |              |       |          |                     |
|         | A DOMESTICS   |   |                    |             |              |              |       |          |                     |
| A       | Cable Length: 5 m   | in private A                              | IIIL N             | HIELDEN,    | Threat I     | 17110000     |       |          |                     |
| A       | Lances: Lance   | MATERIAL STATE                            | 1 7 5              | T L ABY     | THE STATE OF | 1 200        | 100   | 100      | ACCUPATION OF       |
| A       | Handle Type:  |   |                    |             |              |              |       |          |                     |
|         | Folding   | CHERTSHIP                                 | THIA E             | HIG1 0      | TAGISOR      |              |       |          |                     |
| A       | Handle Height: 0.87   |   |                    |             |              |              |       |          | rate who            |
|         |   |   |                    |             |              |              |       |          |                     |
|         | m   | THU                                       | ALC: TO            |             |              |              |       | CIO      |                     |
| A       | Hose Length: 6 m  |   |                    |             |              |              |       |          |                     |
| >       | Hose Type: PVC  |   |                    |             |              |              |       | The same | DE L                |
| >       | Hose Reel: Manual   |   |                    |             |              |              |       |          |                     |
| >       | Weight: 7.9 kg.   |   |                    |             |              |              |       |          |                     |
| >       | Machine Weight:   | of white the mo                           | minis              | part from   | La all n     |              |       |          |                     |
| -       |   |   |                    |             |              | -            |       |          | 1C                  |
|         | 8.42 kg.  | DCD 000 00                                | 2                  | Unit        |              |              |       |          |                     |
| . Elec  | tric Waterpump  | ₱62,000.00                                | 2                  | Onit        |              | factored "   |       | 1        | -8 - 1              |
| A       | 1.5HP Shallow Well  |   |                    |             | the state of |              |       | 1        | 100                 |
|         | Jet Pump  |   |                    |             |              |              |       |          |                     |
| A       | 1.5 Horsepower, 60  | publicated for a                          | THE REAL PROPERTY. |             | The street   | Common 1     |       |          |                     |
|         | Hz Frequency,   |   |                    | me'i libin  | plant of     | 10           |       |          |                     |
|         | 마스트를 보고 있는 이번 기계 전략을 보고 있다면 보고 있다. 그 100 HTM (1997) |   |                    |             |              |              |       |          |                     |
|         | Single Phase,   | earnstar not                              | is burling         | min a 1     | Butt th      |              | 101   | 1111     |                     |
|         | 115/230 V Capacitor   |   |                    |             |              |              |       |          |                     |
|         | Start, 3500 RPM   |   |                    |             |              |              |       |          |                     |
| A       | Pipe Connections: 1   |   |                    |             | FILT THE     |              |       |          |                     |
|         | 1/4" NPT suction, 1"  | de la |                    | VF          |              | lan II.at    |       | 4 D      |                     |
|         | NPT discharge   |   |                    |             |              |              |       |          |                     |
|         |   |   |                    | 1 1         | TON GALLINI  |              |       |          |                     |
| >       | Maximum Shut-off  |   |                    | l design    | de financia  |              | 11115 |          |                     |
|         | Pressure: 80 PSI  |   |                    |             |              |              |       |          |                     |
| A       | Pump Casing: Cast   | 7   |                    |             |              |              |       |          |                     |
|         | Iron  | COS VITA                                  |                    |             |              |              |       |          |                     |
| 1       | Impeller Metal:   |   |                    |             |              |              |       |          |                     |
| A       |   |   |                    |             |              |              |       |          |                     |
|         | Glass Filled Noryl  |   |                    |             |              |              |       |          |                     |
| >       |   |   |                    |             |              |              |       |          |                     |
|         | least 19-1/4  |   | 121 90             | 1           |              |              |       |          |                     |
| A       | <b>Built-in Overload</b>  |   |                    |             | l N D        | The state of |       |          | 1.11                |
| 855     | with Automatic  |   |                    |             |              |              |       |          |                     |
|         | Reset   | THO                                       |                    |             | 0.0          | Tab.         |       | - 0      | 1140                |
| 140     |   | 12  | 193                |             |              | 11111        |       |          |                     |
| A       |   |   |                    |             |              |              |       |          |                     |
|         | Shaft   |   |                    |             | - Total      | distant      |       |          |                     |
| A       | Thermal   |   |                    |             |              | MA.          |       |          |                     |
|         | Protection: Yes   | the street                                |                    |             |              |              |       |          |                     |
| A       | Nozzle clean out  | 131                                       |                    |             |              |              |       |          |                     |
|         |   |   |                    | or or other | in thus      | 12.11        |       | 7        | 34 . 31             |
| ) Ges   | plug in pump case   |   |                    |             |              |              | 117   | 11 1 2   | on I in             |
| >       | Corrosion resistant   |   |                    | 100         |              | -            |       |          |                     |
|         | ustrial Fan   | ₱10,000.00                                | 2                  | Unit        |              |              |       |          |                     |
| 3. Indi | ustriai raii  | 1 10,000.00                               | -                  |             | 1            | 1            |       | 1        |                     |





|          |                                       |            |   | Г    |         |         |           |         |
|----------|---------------------------------------|------------|---|------|---------|---------|-----------|---------|
|          | Fan                                   |            |   |      |         |         |           |         |
| >        | Power: 90 W<br>Air Volume: 115        |            |   |      |         |         |           |         |
|          | m3/min                                |            |   |      |         |         | 1 1 10    |         |
| -        |                                       |            |   |      |         |         | 1         |         |
| 4        | Speed: 1,600 RPM<br>Noise Level: 55dB |            |   |      |         |         |           |         |
| A        | Features: Built-in                    |            |   |      | 100 000 |         |           |         |
| -        | 면 이렇지게 방로면 있는데 있었다. 그리아 아이를 다고 있다     |            |   |      |         |         |           |         |
|          | Thermal Fuse, Solid                   |            |   |      |         | 4       |           |         |
|          | Round Base                            | ₱16,000.00 | 2 | Unit |         |         |           |         |
|          | urement of Vacuum                     | F10,000.00 |   | Ome  |         |         | 4         |         |
| Cleane   | 32 Liter Capacity                     |            |   |      |         | -       |           |         |
| -        | with 3-in-1                           |            |   |      |         |         |           |         |
|          | function: Wet, Dry                    |            |   |      |         | 0.0     |           |         |
|          | & Blow Function                       |            |   |      |         |         | 7100      |         |
| <b>A</b> |                                       |            |   |      |         | 1 1     |           |         |
|          | Wattage: 1,500                        |            |   |      |         |         | 10 11     |         |
| A        |                                       |            |   |      |         |         |           | 1 10000 |
|          | power, Stainless                      |            |   |      | 11      |         | M I       |         |
|          | steel body, Extra                     |            |   |      |         |         |           |         |
|          | filter/deodorizer                     |            |   |      |         | 1 1     |           | 175     |
| >        | Accessories                           |            |   |      |         | 0.7     | ni buniti | 10000   |
|          | included: Extension                   |            |   |      |         |         |           |         |
|          | plastic tube, hose                    |            |   |      | 1       |         |           | 100     |
|          | assembly, dust                        |            |   |      |         |         |           |         |
|          | filter, small nozzle,                 |            |   |      |         |         |           |         |
|          | small brush, hard                     |            |   |      |         |         |           |         |
|          | floor nozzle and big                  |            |   |      |         | 711     |           | Jun.    |
|          | brush                                 |            |   |      |         |         |           |         |
| >        | Dimensions LxWxH:                     |            |   |      |         |         |           |         |
|          | 38.5 x 32 x 59 cm                     |            |   |      |         |         |           |         |
| 5. Reci  | procating Saw                         | ₱4,735.00  | 1 | Unit |         |         |           |         |
|          | / Duty)                               |            |   |      |         |         |           |         |
| A        | Power: 900W                           | 1          |   |      |         |         |           |         |
| >        | Voltage: 220-240V                     |            |   |      |         |         |           |         |
| A        | No-load Speed: 0-                     |            |   |      |         |         |           |         |
|          | 3200 RPM                              |            |   |      |         |         |           |         |
|          | Weight: 3.2 kg.                       |            |   |      |         |         |           |         |
| >        | _                                     |            |   |      |         |         |           |         |
|          | 148mm                                 |            |   |      |         |         |           |         |
| A        | Special Features:                     |            |   |      |         |         |           |         |
|          | Easy twist tool-free                  |            |   |      |         |         |           |         |
|          | blade change<br>Tooled shoe           |            |   |      |         |         |           |         |
|          |                                       |            |   |      |         |         |           |         |
| 6 4      | adjustment                            | ₱2,500.00  | 1 | Unit |         |         |           |         |
|          | le Grinder 4"<br>Power: 820 Watts     | 12,500.00  | ' | Jine |         |         |           |         |
|          | Speed: 11,000 RPM                     |            |   |      |         | 100 991 |           |         |
|          | Spindle Size: M10                     |            |   |      |         |         | 2 2       |         |
| 2        | Power Source:                         |            |   |      |         | 15/101  | e n Ohi   | 2 1     |
|          | Corded Electric, 2-                   |            |   |      |         |         |           | 1.6     |
|          | meter cable                           |            |   |      |         |         | 7         |         |
| D        | Cutting Wheel Size:                   |            |   |      |         |         |           | 面社      |
|          | 4"                                    |            |   |      |         |         |           | 3.0     |
|          | 10 m. 1                               | 3          |   | 1    |         |         |           |         |
| A        | Materials:                            |            |   | 1 1  | 1       |         |           |         |





| >        | Color" Black and            |            |   |        |        |        |         |                 |
|----------|-----------------------------|------------|---|--------|--------|--------|---------|-----------------|
|          | Orange                      |            |   |        |        | 1      |         | 165             |
| A        | Other Features:             |            |   |        |        |        |         |                 |
|          | Spindle Lock,               |            |   |        |        |        |         |                 |
|          | On/Off Slider Type          |            |   |        |        |        |         |                 |
|          | Switch                      |            |   |        |        |        | -       |                 |
|          |                             | ₱5,365.00  | 1 | Unit   |        | 1      |         | and the         |
|          | nmer Drill                  | P5,305.00  |   | Oilit  |        |        |         |                 |
| <b>A</b> | Power: 710 W                |            |   |        |        |        |         |                 |
| >        | Concrete: 16 mm             |            |   |        |        |        |         |                 |
|          | (5/8")                      |            |   |        |        |        |         |                 |
|          | Steel: 13 mm (1/2")         |            |   |        |        |        |         |                 |
| <b>A</b> | Wood: 30 mm (1-             |            |   |        |        |        |         |                 |
|          | 3/16")                      |            |   |        |        |        |         |                 |
| >        | Chuck Capacity: 1.5         |            |   |        |        |        |         |                 |
|          | – 13 mm                     |            |   |        |        |        |         |                 |
| A        | Blows Per Minute            |            |   |        |        |        |         |                 |
|          | (BPM): 0-                   |            |   |        |        |        |         |                 |
| >        | No Load Speed               |            |   |        |        |        |         |                 |
|          | (RPM): 0 - 3,200            |            |   |        |        |        | 111     |                 |
|          | Vibration Level:            |            |   |        |        |        |         |                 |
| >        | Hammer Drilling             |            |   |        |        |        |         |                 |
|          | into Concrete: 17.0         |            |   |        |        |        |         |                 |
|          | m/s <sup>2</sup>            |            |   |        |        |        |         |                 |
| >        | <b>Drilling into Metal:</b> |            |   |        |        |        | Tar T   |                 |
|          | 2.5 m/s <sup>2</sup>        |            |   |        |        | 77-14  | yastı   |                 |
| >        | Dimensions                  |            |   |        |        |        |         |                 |
|          | (LxWxH):                    |            |   | 1      |        |        |         |                 |
|          | 296x75x204mm (11-           |            |   |        |        |        |         |                 |
|          | 5/8" x 2-15/16" x 8")       |            |   |        |        |        |         |                 |
| >        | Net Weight: 2.1 kg.         |            |   |        |        |        | 31.01   |                 |
|          | (4.6 lbs.)                  |            |   |        |        |        |         |                 |
| >        | Power Supply Cord:          |            |   | lett I | 000    | ====   | E ALL T |                 |
|          | 2.0 m (6.6 ft.)             |            |   |        |        |        |         |                 |
| >        | Features: 360°              |            |   | 1      |        |        |         |                 |
|          | Swivel side handle,         |            |   |        |        | 180.00 |         |                 |
|          | 2-mode operation            |            |   |        |        |        |         |                 |
|          | for "Rotation Only"         |            |   |        |        |        |         |                 |
|          | or "Hammering               |            |   |        |        |        | 1 1 1   |                 |
|          | with Rotation" for          |            |   |        |        |        | 100     |                 |
|          | multiple                    |            |   |        |        |        |         |                 |
| 8. 14"   | <b>Cut-Off Machine</b>      | ₱11,000.00 | 1 | Unit   |        |        | 1       |                 |
| >        | Power: 2,200 W              |            |   |        |        |        |         |                 |
| >        | Wheel Diameter:             |            |   |        |        |        |         |                 |
|          | 355 mm (14")                |            |   |        |        |        |         |                 |
| >        | No Load Speed:              |            |   |        |        |        |         |                 |
|          | 3,800 RPM                   |            |   | Anna I | 0.1047 |        |         | 44 441          |
| >        | Capacity at 90°:            |            |   |        |        |        |         |                 |
|          | Round: 127 mm (5")          |            |   |        |        |        |         |                 |
|          | Rectangular:                |            |   |        |        |        |         |                 |
|          | 115x130 mm (4-1/2"          |            |   |        |        | _==#   | LIE T   |                 |
|          | x 5-1/8")                   |            |   |        |        |        |         | MATERIAL STATES |
|          | Rectangular:                |            |   |        |        |        |         |                 |
|          | 102x194 mm (4"x7-           |            |   |        |        |        |         | 102             |
|          | 5/8")                       |            |   |        |        |        |         |                 |
|          | Rectangular:                |            |   |        |        |        |         |                 |
|          | 70x233 mm (2-3/4"           |            |   |        |        |        |         |                 |







| x9-1/8") Square: 119x119 mm (4-11/16"x4- 11/16") Triangular: 137x137x10 mm (5- 3/8"x 5-3/8"x3/8") Capacity at 45°: Round: 127 mm (5") Rectangular: 115x103 mm (4- 1/2"x4-1/16") Square: 106x106 mm (4-3/16"x4- 3/16") Triangular: 100x100x10 mm (4"x4"x3/8") Vibration Level: 2.5 m/s² or less Dimensions (L x W x H): 500x295x640 mm (19-3/4" x 11- 5/8" x 25-1/4") Net Weight: 18.3 kg. (40.3 lbs.) Power supply cord: |           |   |      | 00.00                                   |      |    |     |
|--|-----------|---|------|---|------|----|-----|
| 2.5 m (8.2 ft.)  > Includes; Abrasive wheel, wrench  |           |   |      |   | 1.2  | 70 |     |
| 9. Circular Saw 7"   | ₱4,950.00 | 1 | Unit |   |      |    |     |
| <ul> <li>Wattage: 1,600 Watts</li> <li>No Load Speed: 5,500 RPM</li> <li>Bevel Capacity: 45</li> </ul>   |           |   |      |   | 1    |    |     |
| degrees  Max Cutting Capacity: 65 mm  Max Cutting Capacity at 45 degrees: 50 mm  |           |   |      |   | 1    |    |     |
| <ul> <li>Blade Bore: 20/25.4 mm</li> <li>Blade Diameter: 7"/185 mm; 24 tooth</li> <li>Cable Length: 4m</li> <li>Dimensions LxWxH: 33.5 x 26.5 x 20.5</li> </ul>  |           |   |      |   | (pt. |    |     |
| cm 10. Digital Measuring Wheel  Folded size: 700x320mm  Unfolded format:   | ₱3,000.00 | 1 | Unit | 000000000000000000000000000000000000000 |      |    | X . |





|          | TOTAL ABC   | ₱277,900.00 |   |      |       |       | П       | -       |       |
|----------|---|-------------|---|------|-------|-------|---------|---------|-------|
|          | curement of Shovel Duty for Area 1 Pointed with wooden handle | ₱6,650.00   |   | Onic | Tires | GO FA |         | 4-1-    |       |
| >        | 240mm<br>Dry Weight: 3.33 kg.                                 | DG CEO 00   | 7 | Unit |       |       |         |         |       |
| <b>A</b> | Dimensions: At<br>least 1,928 x 234 x                         |             |   |      |       |       |         |         |       |
| >        | Engine Oil Capacity:<br>0.1 liters                            |             |   |      |       |       | 15      | THE 2   |       |
|          | Mist  |             |   |      |       |       |         |         |       |
| <b>A</b> | 0.63 liters<br>Lubrication: Oil                               |             |   |      |       |       |         | E MISS  | - 1   |
|          | Starter: Recoil Fuel Tank Capacity:                           |             |   |      |       |       | ===     |         | ne)   |
|          | Transistorized  |             |   |      |       |       | nie e   |         |       |
| A        | 5500 RPM<br>Ignition System:                                  |             |   |      |       |       | -       | 61      |       |
| A        | Max. Net Torque:<br>1.6Nm/0.16kgfm/                           |             |   |      |       |       | rt-     | > 4     |       |
| A        | Net Power: 1.0 kw<br>(1.3Hp)/7000rpm                          |             |   |      |       |       | L       |         |       |
| >        | Compression<br>Ration: 8.0:1                                  |             |   |      |       |       | Deiri   |         | ar Vi |
|          | cm  |             |   |      |       |       | TE III  |         |       |
| >        | 30 mm<br>Displacement: 35.8                                   |             |   |      |       |       |         | X 111 B |       |
| >        | Engine<br>Bore x Stroke: 39 x                                 |             |   |      |       |       | on otio | p = 179 |       |
|          | Stroke, Petrol  |             |   |      |       |       | de d    |         | me e  |
| utter    | for Area 1<br>Engine Type: 4-                                 |             |   |      |       |       | ry u    |         |       |
| 1. Pro   | batteries included<br>curement of Grass                       | ₱140,000.00 | 7 | Unit |       |       |         | N M     |       |
| >        | +45°C<br>Batteries: 2 LR3                                     |             |   |      |       |       |         | 711     |       |
| >        | temperature: 10°C -   |             |   |      |       |       |         |         |       |
|          | 0.1 m<br>Working  |             |   |      |       |       |         | PAR I   |       |
| <b>A</b> | Memory: Yes Display Resolution:                               |             |   |      |       |       |         |         | 170 m |
| >        | inch dual system<br>Digital Display &                         |             |   |      |       |       |         |         |       |
|          | Range: 0 - 9999<br>million, metric and                        |             |   |      |       |       | 11 -    | T. LIF  | 117   |
| >        | Measurement   |             |   |      |       |       |         | T be    | -111  |
| >        | Telescopic handle:<br>Yes                                     |             |   |      |       |       |         | LIFE X  |       |
|          | that adapts to most surfaces                                  |             |   |      |       |       |         |         |       |
|          | diameter wheel, with rubber coating                           |             |   |      |       |       |         |         |       |
| >        | Wheel: 320 mm   |             |   |      |       |       |         |         |       |





| GRAND TOTAL: |  |  |  |
|--------------|--|--|--|

Note: Quotation for each item must not exceed the ABC per item (\*\*\*This is a per item procurement\*\*\*)

Signature over Printed Name Supplier/Dealer/Contractor

#### **TERMS AND CONDITIONS**

- 1. Bidders shall provide correct and accurate information required in this form.
- Price quotation/s must be valid for a period of Thirty (30) calendar days from the date of submission.
- Price quotation/s shall be denominated in Philippine Peso which includes all taxes, duties and/or levies payable.
- Quotations exceeding the ABC shall be rejected.
- 5. Award of contract shall be made to the lowest quotation (for goods and infrastructure) or, the highest rated offer (for consulting services) which complies with the minimum technical specifications and other terms and conditions stated herein. Further, the most advantageous to the government to the point of quality of materials and prices as well as the responsiveness of the bids shall be the basis of the award.
- The Head of the Procuring Entity reserves the right to reject any and all bids, declare a failure of bidding or not award the contract in any of the following conditions set forth by Sec. 41 (Reservation Clause) of the Revised IRR of RA 9184.
- The Supply Office of LIA shall have the right to inspect and to test the goods to confirm their conformity to the technical specifications.
- Date of Completion/Delivery: In case of an approved POW, within the period stated therein.
  While, in cases of regular procurement, within 7-10 days or less, after the issuance of the
  Purchase Order. Further, any request of extension shall be sent to the End-User/Implementing
  Facility concern.
- Mode and Terms of Payment: Within ten (10) working days after the supplies/materials and labor/service have been inspected and accepted, respectively, through a check issued by the procuring entity.
- 10. Liquidated damages equivalent to one tenth of one percent (0.001%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. This Office (LIA) shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.

NOTE: The aforecited Terms and Conditions shall be without prejudice to any provisions of a Contract which will be executed by and between the Procuring Entity and Contractor/Supplier/Dealer in order to conform with the requirements set forth by RA 9184.

