



Republic of the Philippines
CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

DATE: December 23, 2024

The **CIVIL AVIATION AUTHORITY OF THE PHILIPPINES-AREA X**, through its Canvass and Contract Committee (CCC), now invites interested contractors/ suppliers to submit their Price Quotations for the Project **PROCUREMENT OF PHOTOCOPIER AND PRINTERS**, with their quantities, and for their respective use and end user:

Quantity/ Unit	Items	Purpose	Office/ Unit/ Airport User	Approved Budget of Contract
7 Units	<p>Wi-Fi All-In-One Ink Tank Printer with ADF</p> <p>Specifications:</p> <p>Printer Type: Print, Scan, Copy, Fax</p> <p>Printing Technology:</p> <p>Print Method: On-demand inkjet (Pi</p> <p>Printer Language: ESC/P-R, ESC/P R</p> <p>Nozzle Configuration:</p> <p>180 x 1 nozzles Black, 59 x 1 nozzles Yellow)</p> <p>Maximum Resolution: 5760 x 1440 d</p> <p>Print Speed:</p> <p>Photo Default - 10 x 15 cm / 4 x 6 " " *</p> <p>Approx. 69 sec per photo (Border) /</p> <p>Draft, A4 (Black / Colour):</p> <p>Up to 33 ppm / 15 ppm*2</p> <p>ISO 24734, A4 Simplex (Black / Cold</p> <p>Up to 10 ipm / 5.0 ipm*2</p> <p>First Page Out Time from Ready Mo</p> <p>Approx. 10 sec / 16 sec*2</p> <p>Copying:</p> <p>Maximum Copies from Standalone;</p> <p>Reduction / Enlargement: 25 – 400 %</p> <p>Maximum Copy Resolution: 600 x 60</p> <p>Maximum Copy Size: Legal</p> <p>ISO 29183, A4 Simplex Flatbed (Black</p> <p>Up to 7.7 ipm / 3.8 ipm</p> <p>Scanning:</p> <p>Scanner Type: Flatbed colour image</p> <p>Sensor Type: CIS</p> <p>Optical Resolution: 1200 x 2400 dpi</p> <p>Maximum Scan Area: 216 x 297 mm</p> <p>Scanner Bit Depth (Colour):</p> <p>48-bit input, 24-bit output</p> <p>Scanner Bit Depth (Grayscale):</p>	Use for PTB Facilities	CAAP Laguinding an Airport	PhP 250,000.00



Republic of the Philippines
CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

	<p>16-bit input, 8-bit output Scanner Bit Depth (Black & White): 16-bit input, 1-bit output <u>Scan Speed:</u> Scan Speed (Flatbed / ADF (Simplex)): 200dpi, Black: 12 sec / Up to 4.5 ipm 200dpi, Colour: 29 sec / Up to 4.5 ipm ADF Specifications: Support Paper Thickness: 64 – 95 g/m2 Paper Capacity: 30 pages (A4), 10 pages (Legal) I.T. Personnel, MIS Fax Function: Type Of Fax: Walk-up black-and-white and colour fax capability Receive Memory / Page Memory: 1.1 MB, Page memory up to 100 pages Error Correction Mode: ITU-T T.30 Fax Speed (Data Transfer Rate): Up to 33.6 kbps, Approx. 3 sec/page Fax Resolution: Up to 200 x 200 dpi Transmission Paper Size (Flatbed): Letter, A4 Transmission Paper Size (ADF): A4, Letter, 8.5 x 13", Legal, Oficio 9, Mexico-Oficio, Indian-Legal Receiving Paper Size: A4, Letter, Legal Speed Dial / Group Dial: Up to 100 numbers, 99 groups Fax Features: PC Fax (Transmission / Receive), Automatic Redial, Address book, Broadcast Fax (Mono Only), Transmit Reservation, Polling Reception Paper Handling: Number of Paper Trays: 1 Standard Paper Input Capacity: Up to 100 sheets of Plain paper (80 g/m2) Up to 20 sheets of Premium Glossy Photo Paper Output Capacity: Up to 30 sheets of Plain Paper (80 g/m2) Up to 20 sheets Premium Glossy Photo Paper Maximum Paper Size: 215.9 x 1200 mm Paper Size: Legal (8.5 x 14"), Indian-Legal (215 x 345 mm), 8.5 x 13", Letter, A4, 16K (195 x 270 mm), B5, A5, B6, A6, Hagaki (100 x 148 mm), 5 x 7", 5 x 8", 4 x 6", Envelopes: #10, DL, C6 Print Margin:</p>			
--	---	--	--	--



Republic of the Philippines

CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

	<p>0 mm top, left, right, bottom via custom settings in printer driver *3</p> <p>Mobile and Cloud Solutions: iPrint, Email Print, Remote Print Driver</p> <p>Other Mobile Solutions: Apple AirPrint, Smart Panel, Mopria Print Service</p> <p>Supported OS and Applications: Operating System Compatibility: Windows XP / XP Professional / Vista / 7 / 8 / 8.1 / 10 Windows Server 2003 / 2008 / 2012 / 2016 / 2019 Only printing functions are supported for Windows Server OS Mac OS X 10.6.8 or later</p> <p>Noise Level: PC Printing/ Premium Glossy Photo Paper Best Photo: Sound Power (Black / Colour) 5.1 / 5.1 B(A), Sound Pressure (Black / Colour) 38 dB(A) / 38 dB(A) PC Printing / Plain Paper Default*4: Sound Power (Black / Colour) 6.3 B(A) / 6.2 B(A), Sound Pressure (Black / Colour) 51 dB(A) / 48 dB(A)</p> <p>Dimensions and Weight: Dimensions (W x D x H): 375 x 347 x 237 mm I.T. Personnel, MIS Weight: 5.0 kg Consumables: Black Ink Bottle: Page Yield*5: 4,500 Pages Order Code: 003 (C13T00V100/ C13T00V199 (Indonesia)) Cyan Ink Bottle: Page Yield*5: 7,500 Pages (Composite Yield) Order Code: 003 (C13T00V200 / C13T00V299 (Indonesia)) Magenta Ink Bottle: Page Yield*5: 7,500 Pages (Composite Yield) Order Code: 003 (C13T00V300 / C13T00V399 (Indonesia)) Yellow Ink Bottle: Page Yield*5: 7,500 Pages (Composite Yield) Order Code: 003 (C13T00V400 / C13T00V499 (Indonesia))</p> <p>Electrical Specifications: Rated Voltage: AC 220 – 240 V Rated Frequency: 50 – 60 Hz Operating: 12 W; Sleep: 0.7 W Power Off: 0.2 W; Standby: 4.5 W</p> <p>Interface: USB:2.0; Network: Ethernet, Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct; Network Protocol: TCP/IPv4, TCP/IPv6 Network Management Protocols:</p>	
--	---	--



Republic of the Philippines

CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

<p>1 Unit</p>	<p>SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD</p> <p>24-Pin Narrow Carriage Impact Dot Matrix Printer for Check Specifications:</p> <p>Includes Ribbon Cartridge (Black for Narrow carriage 24-pin SIDM)</p> <p>High 416 CPS print speed at 12CPI</p> <p>10,000 power on hour MTBF</p> <p>USB, Serial and Parallel ports</p> <p>Ability to create up to a 4-part form original + 3 copies)</p> <p>Print Method: Impact dot matrix</p> <p>Control Panel: 4 switches and 5 LED</p> <p>Print Direction: Bi-direction with log</p> <p>Number of Pins in Head: 24 pins</p> <p>Control Code: ESC/P2 and IBM PPDS</p> <p>Print Speed:</p> <p>High Speed Draft: 10cpi: 347 cps; 12</p> <p>Draft: 10cpi: 260 cps; 12cpi: 312 cps</p> <p>(Condensed) 17cpi: 222 cps; (Conde</p> <p>cps</p> <p>Letter Quality: 10cpi: 86 cps; 12cpi: 129 cps</p> <p>(Condensed) 17cpi: 147 cps; (Conde</p> <p>cps</p> <p>Reliability:</p> <p>MTBF: Approx. 10,000 POH (25% Du</p> <p>Printhead Life: Approx. 400 million s</p> <p>Mean Print Volume Between Failure</p> <p>Approx. 20 million lines (Except prin</p> <p>Paper Path:</p> <p>Manual Insertion: Rear in, Top out</p> <p>Push Tractor: Rear in, Top out</p> <p>Paper Media: Cut Sheet (Single Shee</p> <p>Length: 100 ~ 364 mm (3.9 ~ 14.3")</p> <p>Width: 100 ~ 257 mm (3.9 ~ 10.1")</p> <p>I.T. Personnel, MIS</p> <p>Thickness: 0.065 ~ 0.14 mm (0.0025</p> <p>Cut Sheet (Multi-part Forms):</p> <p>Length: 100 ~ 364 mm (3.9 ~ 14.3")</p> <p>Width: 100 ~ 257 mm (3.9 ~ 10.1")</p> <p>Thickness: 0.12 ~ 0.32 mm (0.0047 ~</p> <p>Envelope (No.6):</p> <p>Length: 92 mm (3.6"), Width: 165 mm</p> <p>Thickness: 0.16 ~ 0.52 mm (0.0063 ~</p> <p>Envelope (No.10):</p>			
---------------	---	--	--	--



Republic of the Philippines
CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

<p>1 Unit</p>	<p>Length: 105 mm (4.1"), Width: 241 mm (9.5"), Thickness: 0.16 ~ 0.52 mm (0.0063 ~ 0.0205") (Total) Continuous Paper (Single Sheet): Length: 101.6 ~ 558.8 mm (4.0 ~ 22.0") Width: 101.6 ~ 254.0 mm (4.0 ~ 10.0") Thickness: 0.065 ~ 0.32 mm (0.0025 ~ 0.0126") (Total) Continuous Paper (Multi-part Forms): Length: 101.6 ~ 558.8 mm (4.0 ~ 22.0") Width: 101.6 ~ 254.0 mm (4.0 ~ 10.0") Thickness: 0.065 ~ 0.32 mm (0.0025 ~ 0.0126") (Total) Roll Paper: Width: 216 mm (8.5"), Thickness: 0.07 ~ 0.09 mm (0.0028 ~ 0.0035") General: Memory Buffer: 128KB Supported OS and Applications: Supported OS: Windows 95 / 98 / 2000 / Me /XP / Vista / 7 / 8 / 8.1 / 10 Utility: Epson Status Monitor 3: Microsoft® Windows® 2000 / XP / 7 / 8 / 8.1 / 10 Epson Printer Setting: Microsoft® Windows® 2000 / XP / 7 / 8 / 8.1 / 10 Dimensions (W x D x H): 362 x 275 x 154 mm Weight: 4.1kg Consumables: Ribbon Cartridge Black: LQ-310 Approx. 2.5 million characters (LQ 10cpi, 48 dots/character) - C13S015639 Options: Fabric Ribbon Cartridge (Black) - S015634 Interface: Bi-directional parallel interface (IEEE-1284 nibble mode supported) USB 2.0 Full-Speed; Serial 9-Pin Narrow Carriage Impact Dot Matrix Printer for Carbonless Paper (Receipt) Specifications: Includes Ribbon Cartridge (Black for Highly reliable printing with better p Narrow carriage 9-pin SIDM High 357 CPS print speed at 12CPI 10,000 power on hour MTBF USB, Serial and Parallel ports Ability to create up to a 5-part form 4 copies). Print Method: Impact dot matrix Control Panel: 4 switches and 5 LED</p>
---------------	---



Republic of the Philippines

CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

	<p>Print Direction: Bi-direction with logic seeking</p> <p>Number of Pins in Head: 9 pins</p> <p>Control Code: ESC/P and IBM PPDS emulation</p> <p>Number of Pins: 9</p> <p>Print Speed:</p> <p>I.T. Personnel, MIS</p> <p>High Speed Draft: (10 / 12 / 15 cpi): 347 / 357 / 390 cps</p> <p>(Condensed, 17 / 20 cpi): 383 / 298 cps</p> <p>Draft: (10 / 12 / 15 cpi): 260 / 312 / 223 cps</p> <p>(Condensed, 17 / 20 cpi): 222 / 260 cps</p> <p>(Emphasized, 10 cpi): 130 cps</p> <p>NLQ: (10 / 12 / 15 / 17 / 20 cpi): 65 / 78 / 55 / 47 / 56 cps</p> <p>Reliability:</p> <p>Printhead Life: Approx. 400 million strokes/wire</p> <p>Mean Print Volume Between Failure (MVBF):</p> <p>Approx. 20 million lines (Except print head)</p> <p>Mean Time Between Failure (MTBF): Approx. 10,000 POH (25% Duty)</p> <p>Paper Path:</p> <p>Manual Insertion: Rear in, Top out</p> <p>Push Tractor: Rear in, Top out</p> <p>Paper Media: Cut Sheet (Single Sheet):</p> <p>Length: 100 ~ 364mm (3.9 ~ 14.3")</p> <p>Width: 100 ~ 257mm (3.9 ~ 10.1")</p> <p>Thickness: 0.065 ~ 0.14mm (0.0025 ~ 0.0055")</p> <p>Cut Sheet (Multi-part Forms):</p> <p>Length: 100 ~ 364mm (3.9 ~ 14.3")</p> <p>Width: 100 ~ 257mm (3.9 ~ 10.1")</p> <p>Thickness: 0.12 ~ 0.39mm (0.0047 ~ 0.015") (Total)</p> <p>Continuous Paper (Single Sheet / Multi-part):</p> <p>Length: 101.6 ~ 558.8mm (4.0 ~ 22.0")</p> <p>Width: 101.6 ~ 254.0mm (4.0 ~ 10.0")</p> <p>Thickness: 0.065 ~ 0.39mm (0.0025 ~ 0.015") (Total)</p> <p>Envelope (No.6): Length: 92mm (3.6"); Width: 165mm (6.5")</p> <p>Thickness: 0.16 ~ 0.52mm (0.0063 ~ 0.0205") (Total)</p> <p>Envelope (No.10): Length: 105mm (4.1"); Width: 241mm (9.5")</p> <p>Thickness: 0.16 ~ 0.52mm (0.0063 ~ 0.0205") (Total)</p> <p>Roll Paper: Width: 216mm (8.5")</p> <p>Thickness: 0.07 ~ 0.09mm (0.0028 ~ 0.0035")</p> <p>Supported OS:</p> <p>Microsoft® Windows® 2000 / XP / Vista / 7 / 8 / 8.1 / 10</p> <p>Dimensions and Weight: Dimensions (W x D x H): 362 x 275 x 154 mm</p> <p>Weight: Approx. 4.1 kg</p> <p>Consumables: Ribbon Cartridge Black:</p> <p>Ribbon Life: Approx. 4.0 million characters (Draft 10 cpi, 14 dots/character)</p>		
--	--	--	--



Republic of the Philippines

CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

1 Unit	<p>Input Data Buffer: 128KB</p> <p>Interface Standard:</p> <p>Bi-directional parallel (IEEE-1284 nibble mode supported)</p> <p>USB 2.0 Full-Speed; Serial</p> <p>Ribbon Cartridge:</p> <p>Standard: Fabric Ribbon Cartridge (Black) - C135015632</p> <p>Ribbon Life: Approx. 4.0 million characters (Draft 10 cpi, 14 dots/character)</p> <p>Professional Label Printer with</p> <p>Wired, Wireless & Bluetooth</p> <p>Connectivity</p> <p>Includes Paper Label Rolls (DK) for C</p> <p>Print up to 62mm DK rolls width</p> <p>USB, USB host, Bluetooth, Wired LAN</p> <p>connection</p> <p>Auto cut function</p> <p>Standalone print without PC require</p> <p>Fast print speed of up to 176mm pe</p> <p>Stand-alone Time-stamping function</p> <p>I.T. Personnel, MIS</p> <p>Display Type: 320x120 dot graphic L</p> <p>Media Type: DK roll</p> <p>Available Tape Widths: 12 - 62mm</p> <p>Product Dimensions (Width X Depth</p> <p>125.3 mm x 234 mm x 145 mm</p> <p>Weight: 1.16 kg</p> <p>Print Speed: Max 176mm/sec</p> <p>Resolution: Standard: 300 dpi x 300</p> <p>High resolution mode: 300 dpi x 600</p> <p>Barcode: 21 barcode protocols on P</p> <p>Numbering: Yes</p> <p>Connectivity: USB & Wired Ethernet,</p> <p>Bluetooth</p> <p>Media: Maximum Roll Width up to 6</p> <p>Printing Width: Up to 58 mm</p> <p>Functions: Cutter</p> <p>Yes (full auto cut / guillotine type)</p> <p>Multi Block Printing: PC</p> <p>Copy Printing; Yes</p> <p>Mirror Printing: Yes</p> <p>Preview; Yes</p> <p>Power Source: 100-240V AC externa</p> <p>switching)</p> <p>Auto Power-Off: Yes</p> <p>Supported Commands: Raster, ESC/</p> <p>Template</p> <p>Photocopier</p>			
1 Unit				



Republic of the Philippines

CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

	<p>System speed Up to 20 ppm 1st page out time A4 6.5 sec or less Warm-up time 15 sec* or less Imaging technology Laser Toner technology Simitri® HD polymerised toner Panel size/resolution 5 line LCD / 128 x 64 System memory 256 MB System hard drive 256 GB SSD (standard) / 1 TB SSD (optional) Interface 10/100-Base-T Ethernet; USB 2.0 Network protocols TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP ADF double feed detection Optional Printable paper size A5-A3; customized paper sizes Printable paper weight 64-157 g/m2 Paper input capacity 350 sheets / 1,350 sheets (standard/max) Manual bypass 100 sheets; A6-A3; custom sizes, 64-157/m2 Automatic duplexing A6-A3; 64-90 g/m2 Output capacity Up to 250 sheets Duty cycle (monthly) Rec. 25,000 pages; Max.2 150,000 pages Toner lifetime Black up to 25,000 pages Imaging unit lifetime Black up to 245,000/1,000,000 pages (drum/developer) Power consumption 220-240 V / 50/60 Hz; Less than 1.30 kW System dimension (W x D x H) 607 x 570 x 458 mm (without options) System weight 28.2kg (without options) Printer Specifications: Print resolution 600 x 600 dpi Page description language GDI Operating systems Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows I.T. Personnel, MIS Server 2019; Linux Scanner Specifications: Scan speed 150dpi : up to 55/20 ipm in simplex 300dpi : up to 55/8 ipm in simplex Scan resolution Up to 600 x 600 dpi Scan modes Scan-to-eMail; Scan-to-SMB; Scan-to-FTP; Scan-to-USB; TWAIN scan File formats JPEG; TIFF; PDF Scan destinations 32 destinations; 250 speed dials; LDAP support Copier Specifications: Copy resolution 600 x 600 dpi Gradation 256 gradations Multicopy 1-9,999</p>			
--	---	--	--	--



Republic of the Philippines
CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

	<p>Original format Max. A3 Magnification 25-400% in 0.1% steps; Auto-zooming Fax Specification: Fax standard Super G3 (optional) Fax transmission Analogue; i-Fax Fax resolution Up to 408 x 392 dpi Fax compression MH; MR; MMR; JBIG Fax modem Up to 33.6 Kbps Fax destinations 32 destinations; 250 speed dials User Box Specifications: Storable documents Up to 3,000 documents or 10,000 pages Type of user boxes Public; Personal (with password or authentication); Group (with authentication) Type of system boxes Secure print; Encrypted PDF print; Fax receipt; Fax polling</p>			
--	--	--	--	--

Deadline of Submission: December 27, 2024 at 10:00 A.M

Bidding will be conducted through open competitive bidding procedures using a non-discretionary "pass/fail" criterion as specified in the Implementing Rules and Regulations (IRR) of Republic Act (RA) 9184, otherwise known as the "Government Procurement Reform Act".

Further, the prospective suppliers should possess the following:

1. Should have the legal capacity to enter into business or to perfect contracts (with updated Business Permit from DTI and recent Tax Certification from BIR as per Section 8.5 of Section 8.0 of Rule III and as per sub-paragraph a.ii of Section 24.1 of Section 24 of Rule VIII of the Revised IRR of RA 9184 and GPPB Resolution No. 11-2013 dated April 26, 2013);
2. PhilGeps Registration Certificate (At least Red Membership)
3. Notarized Omnibus Sworn Statement
4. Should not be among those blacklisted suppliers. (as per sub- sub-paragraph a.iv (1) of Section 25.2 of Section 25 of Rule VIII of the Revised IRR of RA 9184 and Section 2 of GPPB's UNIFORM GUIDELINES FOR BLACKLISTING OF MANUFACTURERS, SUPPLIERS, DISTRIBUTORS, CONTRACTORS AND CONSULTANTS)

The **CIVIL AVIATION AUTHORITY OF THE PHILIPPINES (CAAP)- AREA X** reserves the right to accept or reject any bid, to annul the bidding process, and to reject all bids at any time prior to contract award, without thereby incurring any liability to the affected bidder or bidders.




Republic of the Philippines
CIVIL AVIATION AUTHORITY OF THE PHILIPPINES

For further information, please refer to:

CAROLINA C. ADANZA

CCC-Secretary
Ground Floor, Admin Building
Laguindingan Airport
Laguindingan, Misamis Oriental
CAAP Area X
Telephone: (088)-555-1881 (Local 1210)
0915-56-89246

Signed:



JOHN ROVELL Z. SIJO
MHCU Chief
CCC Chairperson